

Product datasheet

Specifications



Kavacha - 63A - 440V - Surface Mount triple Pole Isolating Switch - IP66

WHT63_GY

Main

Range	Kavacha
Product or component type	Isolating switch
Device short name	W
Device application	Control

Complementary

[Ie] rated operational current	63 A at 440 V AC-22A
Poles description	3P
Motor Rating	M160
Width	82 mm
Height	170 mm
Depth	90 mm

Environment

IP degree of protection	IP66
Standards	IEC 60947-3
Environmental characteristic	Weatherproof

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	733.333 g
Package 1 Height	17.5 cm
Package 1 width	9 cm
Package 1 Length	8.3 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Weight	22000 g
Package 2 Height	365 mm
Package 2 width	285 mm

Package 2 Length	435 mm
Unit Type of Package 3	P12
Number of Units in Package 3	540
Package 3 Weight	414000 g
Package 3 Height	1300 mm
Package 3 width	800 mm
Package 3 Length	1200 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile