



# V BAY PRO

## โคมไฮเบช์ วีเบช์ โปร แอลอีดี





### **Optical Characteristics**

Туре	Beam angle		
Narrow beam	60°		
Wide Beam	120°		
High rack	60x120		











V Bay Pro LED high bay is a direct replacement of 250W and 400W HID high bay. Offering significant energy saving to Industrial facilities and warehouse area. In the event of power failure downtime are reduced by instant start of V Bay Pro unlike longer run up time in HID lamp. Various type of optics are available to achieve excellent lighting performance in different application areas. Flexible installation via chain or rod mounting.

## **Technical Specifications**

V Bay Pro	100W		200W
Lumen output (lm.)	12,100		24,500
Color		Silver grey	
CRI (Ra)	>75		>75
System Power	100W		200W
System voltage		120-277 VAC 50/60Hz.	
Power Factor	>0.95		>0.95
Operating temp		-25C°-55C°	
IP		66	
LED		Philips LUMILED	
Mounting method		Chain/Rod	
Life time (hrs.)		50,000	

MODEL NO.	D	IMENSIO	ı.)	
WODEL NO.	D	d	Н	Weight (kg.)
V Bay Pro 100W	370	330	160	5.7
V Bay Pro 200W	460	420	160	7.0



- รูปแบบและคุณลักษณะของสินค้าอาจจะมีการเปลี่ยนแปลงได้ โดยไม่จำเป็นต้องแจ้งให้ทราบล่วงหน้า