

VCT-G



TIS 11 Part 101-2553

450/750 V 70°C FLEXIBLE CONDUCTOR PVC INSULATED AND SHEATHED WITH GROUND, ROUND TYPE



CABLE STRUCTURE		TECHNICAL DATA	
Conductor	: Flexible annealed copper Multi-cores : Sizes 4 mm ² up to 35 mm ²	Classification	: Maximum conductor temperature 70°C : Circuit voltage not exceeding 450/750 Volts 450 Volts between Line-to-Earth 750 Volts between Line-to-Line
Ground wire	: Flexible annealed copper Multi-cores : Sizes 4 mm ² up to 16 mm ²	Testing voltage	: 2,500 Volts
Insulation	: Polyvinyl chloride (PVC/D)	Reference standard	: TIS 11 Part 101-2553, Table 8
Core identification	2 Cores : Blue and Brown 3 Cores : Blue, Brown and Grey 4 Cores : Blue, Brown, Black and Grey Ground core : Green/Yellow	APPLICATION	
Sheath	: Black polyvinyl chloride (PVC/ST5)	For mobile-electrical equipment used in mines, factories, farm or household appliances. This cable is suitable for use in places where cables come in contact with oils.	

Number of core	Nominal cross sectional area (mm ²)	Class of conductor	Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ-km)	Continuous current rating in free air maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
2+G	4	5	0.9	1.6	15.5	4.95	0.0084	34	280	100/C
	4 (G)	5	0.9	1.6	15.5	4.95	0.0084	34	280	100/C
	6	5	0.9	1.8	17.5	3.30	0.0071	44	400	100/C
	6 (G)	5	0.9	1.8	17.5	3.30	0.0071	44	400	100/C
	10	5	1.1	2.0	21.5	1.91	0.0068	63	650	500/D
	10 (G)	5	1.1	2.0	21.5	1.91	0.0068	63	650	500/D
	16	5	1.1	2.4	25.0	1.21	0.0050	82	900	500/D
	16 (G)	5	1.1	2.4	25.0	1.21	0.0050	82	900	500/D
	25	5	1.3	2.6	28.5	0.780	0.0048	108	1,200	500/D
	16 (G)	5	1.1	2.6	28.5	1.21	0.0048	108	1,200	500/D
35	5	1.3	2.8	31.5	0.554	0.0041	133	1,500	500/D	
16 (G)	5	1.1	2.8	31.5	1.21	0.0041	133	1,500	500/D	

Class of conductor 5 : Flexible

G : Ground conductor

C : Packing in coil
D : Packing in drum

VCT-G



TIS 11 Part 101-2553

450/750 V 70°C FLEXIBLE CONDUCTOR PVC INSULATED AND SHEATHED WITH GROUND, ROUND TYPE



CABLE STRUCTURE

Conductor	: Flexible annealed copper Multi-cores : Sizes 4 mm ² up to 35 mm ²
Ground wire	: Flexible annealed copper Multi-cores : Sizes 4 mm ² up to 16 mm ²
Insulation	: Polyvinyl chloride (PVC/D)
Core identification	2 Cores : Blue and Brown 3 Cores : Blue, Brown and Grey 4 Cores : Blue, Brown, Black and Grey Ground core : Green/Yellow
Sheath	: Black polyvinyl chloride (PVC/ST5)

TECHNICAL DATA

Classification	: Maximum conductor temperature 70°C : Circuit voltage not exceeding 450/750 Volts 450 Volts between Line-to-Earth 750 Volts between Line-to-Line
Testing voltage	: 2,500 Volts
Reference standard	: TIS 11 Part 101-2553, Table 8

APPLICATION

For mobile-electrical equipment used in mines, factories, farm or household appliances. This cable is suitable for use in places where cables come in contact with oils.

Number of core	Nominal cross sectional area (mm ²)	Class of Conductor	Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ-km)	Continuous current rating in free air maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
3+G	4	5	0.9	1.8	17.0	4.95	0.0084	29	360	100/C
	4 (G)	5	0.9			4.95				
	6	5	0.9	2.0	19.5	3.30	0.0071	38	500	100/C
	6 (G)	5	0.9			3.30				
	10	5	1.1	2.2	24.0	1.91	0.0068	53	800	500/D
	10 (G)	5	1.1			1.91				
	16	5	1.1	2.6	28.0	1.21	0.0050	71	1,200	500/D
	16 (G)	5	1.1			1.21				
	25	5	1.3	2.8	33.0	0.780	0.0048	94	1,600	500/D
	16 (G)	5	1.1			1.21				
35	5	1.3	3.1	37.0	0.554	0.0041	116	2,100	500/D	
16 (G)	5	1.1			1.21					

Class of conductor 5 : Flexible

G : Ground conductor

C : Packing in coil
D : Packing in drum

VCT-G



450/750 V 70°C FLEXIBLE CONDUCTOR PVC INSULATED AND SHEATHED WITH GROUND, ROUND TYPE



CABLE STRUCTURE		TECHNICAL DATA	
Conductor	: Flexible annealed copper Multi-cores : Sizes 4 mm ² up to 35 mm ²	Classification: Maximum conductor temperature 70°C : Circuit voltage not exceeding 450/750 Volts 450 Volts between Line-to-Earth 750 Volts between Line-to-Line	
Ground wire	: Flexible annealed copper Multi-cores : Sizes 4 mm ² up to 16 mm ²		
Insulation	: Polyvinyl chloride (PVC/D)		
Core identification	2 Cores : Blue and Brown 3 Cores : Blue, Brown and Grey 4 Cores : Blue, Brown, Black and Grey Ground core : Green/Yellow	Testing voltage : 2,500 Volts Reference standard : TIS 11 Part 101-2553, Table 8	
Sheath	: Black polyvinyl chloride (PVC/ST5)	APPLICATION	
		For mobile-electrical equipment used in mines, factories, farm or household appliances. This cable is suitable for use in places where cables come in contact with oils.	

Number of core	Nominal cross sectional area (mm ²)	Class of conductor	Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ-km)	Continuous current rating in free air maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
4+G	4	5	0.9	1.8	18.5	4.95	0.0084	29	440	100/C
	4 (G)	5	0.9			4.95				
	6	5	0.9	2.0	21.5	3.30	0.0071	38	600	500/D
	6 (G)	5	0.9			3.30				
	10	5	1.1	2.2	26.5	1.91	0.0068	53	1,000	500/D
	10 (G)	5	1.1			1.91				
	16	5	1.1	2.6	30.5	1.21	0.0050	71	1,400	500/D
	16 (G)	5	1.1			1.21				
	25	5	1.3	2.8	36.5	0.780	0.0048	94	2,000	500/D
	16 (G)	5	1.1			1.21				
35	5	1.3	3.1	41.5	0.554	0.0041	116	2,600	500/D	
16 (G)	5	1.1			1.21					

Class of conductor 5 : Flexible

G : Ground conductor

C : Packing in coil
D : Packing in drum