

Motor Circuit Breakers, GV2 , GV3

คุณสมบัติ

GV2L และ GV3L

มอเตอร์เบรกเกอร์ลูบิต
แบบมีระบบป้องกัน Thermal
และ Magnetic trip



GV2L



GV3L

GV2ME Thermal Magnetic Circuit Breaker for Motor Starters with toggle control

Motor Rating			รหัสสินค้า	ราคา (บาท)
kW at 400 V	HP at 400 V			
0.09		0.4	GV2L03	2,530
0.12	0.17	0.63	GV2L04	2,530
0.18	0.25	0.63	GV2L04	2,530
0.25		0.63	GV2L05	2,530
0.37	0.5	1	GV2L05	2,530
0.55		1.6	GV2L06	2,530
0.75	1	2.5	GV2L07	2,530
1.1		4	GV2L08	2,530
1.5	2	4	GV2L08	2,530
2.2	3	4	GV2L10	2,530
3		10	GV2L14	2,530
4	5.5	10	GV2L14	2,530
5.5	7.5	14	GV2L16	2,860
7.5	10	18	GV2L20	2,860
9	12	25	GV2L21	3,350
11	15	25	GV2L22	3,350
15	20	32	GV2L32	4,410
18.5	25	40	GV2L40	5,720
22	30	50	GV2L50	6,330
30	40	65	GV2L65	6,560